

# AS374

**Sirena antideflagrante de alarma. 32 tonos a 24Vcc/250mA. Roja.**

## General

---

The AS374 is a hazardous area electronic sounder for use in hazardous areas, to provide an audible warning signal in case of fire. It carries EExd IIC T4 rating, and has a marine grade aluminium housing with IP67 rating.

## Hazardous Area

---

The AS374 is ATEX approved with ExII 2G and EExd IIC T4 ratings. It is housed in marine grade aluminium, and offers IP67 ingress protection.

## Efficient and versatile

---

The AS374 provide a high sound output level, which ensures that it can be used indoor and outdoor. The AS374 sounder is supplied with a volume control as standard, allowing final audio adjustments to be made during installation. This allows of the output level to be reduced, when the sounder is used indoors.

With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation. A second and third tone, is available if extra wires are installed in the sounder circuit.



## Details

---

- ATEX approved
- EExd IIC T4 rating
- 32 Tones user selectable
- 2nd and 3rd stage alarm
- IP67
- High output

# AS374

Sirena antideflagrante de alarma. 32 tonos a 24Vcc/250mA. Roja.

## Technical specifications

---

### Físico

---

Peso neto	3.4 kg
Color	Rojo

---

### Medioambiental

---

Temperatura de funcionamiento	-50 to +55°C
Entorno	Exd, Interior, Exterior
Clasificación IP	IP67

---

### Estándares y regulaciones

---

Certificación	CENELEC/ATEX
---------------	--------------

---

### Operation

---

Continuous

---

### Supply voltage

---

24 VDC

---

### Current consumption

---

(see tone table in manual)	250mA typical
----------------------------	---------------

---

### Sound output @ 1 metre

---

(see tone table in manual)	up to 117dB(A)
----------------------------	----------------

---

### Number of tones

---

32

---

### Housing

---

Marine grade LM6 aluminium

---

### Ingress protection

---

IP67

---

### Operating temperature

---

-50°C to +55°C

---

### Dimensions (Ø x D)

---

181 x 262 mm

---

### Weight

---

3.4 Kg

---

### Color

---

Red

---

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 11 February 2019 - 19:12

