

FE245

Retenedor electromagnético de 400N para montaje en pared con pulsador de desbloqueo.

General

The FE245 is a wall mount door holder, in a Bayblend housing, which offers a 400N holding force and a release button.

Magnet construction

The magnet is constructed with a pressed coil and anti-remenance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

Housing

The plastic housing is manufactured from Bayblend and contains 30% PA6 glass fiber, which makes it much stronger than standard ABS. Bayblend offers high heat resistance, high impact and notched impact strength, and high stiffness and dimensional stability.

Installer friendly

- For practical ease of installation, the door holder comes complete with electrical screw terminals.

- The housing is predrilled in a practical, standard format for rapid mounting.

- The door holder is supplied complete with a keeper plate, which offer angular adjustment.

Approvals

The FE245 is fully approved according to EN1155.



Details

- Low power 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- Release button
- EN1155 approved
- Keeper plate included

FE245

Retenedor electromagnético de 400N para montaje en pared con pulsador de desbloqueo.

Technical specifications

General	
Fuerza de retención N	400
(Newtons)	
Botón de liberación	Si
Diodo de supresión de chispa	Yes
Protección contra inversion de polaridad	Yes
Eléctrico	
Tipo de fuente de alimentación	24 VCC
Consumo de corriente	1.6 W
Ciclo de trabajo	100%
Físico	
Dimensiones físicas	70 x 70 x 65 mm (H x W x D)
Medioambiental	
Clasificación IP	IP54 (magnet)
	IP42 (connection)
Estándares y regulaciones	
Normativas	EN1155

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

