

# 6550AM

## 15m/50ft Fresnel PIR/AM

## **DesignLine series - PIR technology**

The DesignLine series is a range of volumetric motion sensor using a PIR element and digital signal processing.

This series is suitable for residential and light commercial environments.

The DesignLine series builds customer value by meeting customers' security needs while respecting budget constraints. This range is quick to install and comes with a stylish housing. It provides detection for a variety of ranges, including up to 360 degrees of coverage for ceiling mount applications and now also an EN Grade 3 certified variant with AntiMasking functionality (6550AM). It even has a variant with smart pet immunity up to 35kg, making this series all the more attractive. These motion sensors deliver easy solutions for installers - being equipped with a standard EOL resistor values (6550AM only) and providing flexibility in installing height are the ideal security solution for residential and light commercial applications.



#### **Standard features**

- Passive infrared volumetric motion sensor with antimasking functionality
- Digital signal processing
- Unique stylish design
- Quick to install
- Built-in EOL resistor of 3k3 and 4k1Ω
- EN50131 Grade 3
- Holds several European security approvals

# **Specifications**

|                            | 6550AM           |
|----------------------------|------------------|
| Detection range            | 15m              |
| Optics                     | Fresnellens      |
| Mounting height            | 1.5 to 3.1 m     |
| Powersupply                | 9to15VDC         |
| Current consumption (nom.) | 21.5mA           |
| Alarmrelay                 | <24 VDC,50mA,NC  |
| Tamperrelay                | <24 VDC,50mA, NC |
| Trouble/Fault relay        | <24 VDC,50mA, NC |
| Target speed range         | 30cm/s to 3m/s   |
| Dimensions (WxHxD)         | 123x66x42mm      |
| Weight                     | 97g              |
| Ambient conditions         | -10 to +55°C     |
| Relative humidity          | Max.95%          |
| EN50131                    | Grade3           |

### **Ordering information**

| Part No. | Description             |
|----------|-------------------------|
| 6550AM   | 15m/50ft Fresnel PIR/AM |