



TVB-6103

TruVision HD-TVI Analog Bullet Camera, 2MPX, 2.7~13.5MM Motorized Lens, True D/N, WDR, 80m IR HD-TVI Output, Coax OSD Control, 12VDC/24AC, IP67

Overview

The TruVision line includes a comprehensive family of HD-TVI infrared (IR) cameras for stand-alone or integrated installations. Designed for optimal image quality over existing coaxial cable, options are available at up to 8Mpx resolution.

Ideal for improving video quality of existing analog surveillance system installations ranging from convenience stores to retail mall parking lots, the TruVision HD-TVI line has the right cameras for your new or existing project and can help you stay within budget constraints without compromising security needs.

The cameras have true day/night capabilities, providing color images by day and black-and-white images under IR operation in low light applications. TruVision HD-TVI cameras are available with either fixed lens or varifocal lens.

Form factors include dome, traditional bullet and turret cameras. Bullet models offer a familiar form factor that features a pre-installed wall mount with cable management. All models are IP67 rated for outdoor installation and select dome models are available with an IK10 vandal-rated enclosure.

All TruVision HD-TVI cameras are designed to install quickly and easily, right out of the box, so you can be up and running in no time.



Details

- 1080p HD resolution
- HD-TVI technology for transmitting HD quality video over existing coax cable
- True day/night functionality and infrared illuminators with Smart IR function for capturing images in various lighting scenarios
- IR range of up to 80 m
- IP67 environmental rating
- True wide dynamic range
- 2.7 to 13.5 mm lens
- 12 VDC or 24 VAC
- Bracket included
- Provide OSD functionality via TruVision up the coax control

TVB-6103

TruVision HD-TVI Analog Bullet Camera, 2MPX, 2.7~13.5MM Motorized Lens, True D/N, WDR, 80m IR HD-TVI Output, Coax OSD Control, 12VDC/24AC, IP67

Technical specifications

General

Technology	HD-TVI analog
Video standard	NTSC, PAL
Image settings	Mirror
Video output	BNC Composite PAL / NTSC, HD-TVI

Camera

Max. resolution	1080p
Sensor scan	Progressive
Sensor type	CMOS
Effective pixels (H x V)	1920 x 1080
Shutter time	1/25s (PAL) or 1/30s (NTSC) to 1/50,000

Lighting performance

WDR type	True WDR
WDR	130 dB
Day/night	True Day/Night
Motorized IR cut filter	Yes
Color sensitivity	0.003 Lux @ (F1.2, AGC ON)
B/W sensitivity	0 Lux with IR
Infrared (IR)	Yes
IR range	80m

Lens

Lens type	Varifocal motorized
Focal length	2.7 to 13.5 mm
f-stop	f1.2
Auto iris	Yes
Auto focus	No
Motorized zoom	Yes

Electrical

Operating voltage	12VDC or 24VAC
Power supply type	12 VDC, 24 VAC
Power consumption	9 W Max.

Physical

Physical dimensions	85 x 92 x 269.6 mm
Net weight	910 g
Colour	Grey (Pantone 428c)
Material	Aluminium
Form Factor	Bullet

Environmental

Vandal proof	No
Environment	Indoor / Outdoor
Operating temperature	-40 to 60°C
Relative humidity	90% or less (non-condensing)
IP rating	IP67

Regulatory

Compliance	CE, REACH, RoHS, WEEE
------------	-----------------------

Compatible TruVision Recorders/Encoders

TVR12HD	(Record Max. 12 fps)
TVR44HD	
TVR15HD	
TVR45HD	
TVR46HD	
TVE-110/410/810/1610	(960H only)
TVE-120/420/820/1620	

Supported Accessories

TVD-M-PMA	Pole Mount Adaptor
TVD-M-CMA	Corner Mount Adaptor

As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 9 June 2021 - 16:04

