



AB304

Xenon Beacon, White base, Red lens

General

The AB304 is a general purpose 1W red xenon beacon which can be used in various applications.

Greater visibility

The AB304 beacon is fitted with a diffuser for greater visibility and spread of light.

Locking mechanism

The mechanism for locking the beacon to the base is activated by default, but can be disabled if required. A special tool is required to remove the beacon from the base, if the locking mechanism is active.

Details

- Anti-Tamper locking mechanism
- Weather proof / IP65
- 12V or 24V

AB304

Xenon Beacon, White base, Red lens

Technical specifications

General

Accessory group	Beacon
Type	Accessory

Flash specifications

Flash frequency	60/min.
-----------------	---------

Electrical

Operating voltage	12 V \pm 15% or 24 V \pm 15%
Current consumption	Average : 75mA @ 12 V or 45 mA @ 24 V; Peak : 95 mA @ 12 V or 50 mA @ 24 V

Physical

Physical dimensions	85 x 81 mm (\varnothing x D)
Net weight	144 g
Material	High impact polycarbonate

Environmental

Operating temperature	-20 to 40°C
IP rating	IP65



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 23 March 2021 - 16:05