

ACT430E-5

(5-pack) Mifare Classic S50 with 7-byte UID (CSN) Keyfob. For use on with ATS1160N/1161N & ACI406/407 Mifare readers.

Product overview

These Mifare Classic 1k keyfobs are to be used on ATS1160N/ATS1161N, ACI406/ACI407 and any other UTC Fire & Security Mifare or Transition reader supporting 7-byte Card Serial Numbers (CSN). The cards are unprogrammed and only the unique 7-byte ID-number of the Mifare® chip, the so called Chip or Card Identification Number (CSN) is used by the readers.



Details

- Read only for CSN (7-byte)
- Read / Write function for card sectors

ACT430E-5

(5-pack) Mifare Classic S50 with 7-byte UID (CSN) Keyfob. For use on with ATS1160N/1161N & ACI406/407 Mifare readers.

Technical specifications

Technology

Credential type	Proximity
Credential operating frequency	13.56 MHz
Supported technology	MIFARE Classic (CSN)
13.56 MHz	

System

Reading distance	0 to 10 cm
Memory size	1 kB
No. of Mifare bytes CSN	7 Byte (S50)
Supported readers	ACI406/407 Mifare Readers, ATS1160/1161 Mifare Readers

Ordering information

Cards/tags in package	1
-----------------------	---

Physical

Material	PA6
Form factor	KeyFob
Physical dimensions	45 x 30 x 14 mm
Net weight	16 g
Colour	Black

Environmental

IP rating	IP66
-----------	------



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 19 August 2020 - 16:46