

AS506

Self-activating outdoor siren with single red beacon



Details

- Attractive high quality shaped housing
- Double piezo sounder with 114 dB @ 1m sound output
- Vertical or horizontal mounting
- Fully potted electronics
- On-board Ni-Cd-battery
- Strobe flash light
- Selectable comfort LED indication
- Pry-off and opening tamper detection
- Self detection of cable cutting or tampering
- Installer friendly
- Hold-off polarity selection
- Independently hold-off for both beacon and siren
- A choice of cut off time
- Selectable tamper configuration

AS506

Self-activating outdoor siren with single red beacon

Technical specifications

General

Accessory group	Siren
Type	Outdoor siren

Electrical

Operating voltage	10 to 14.5 V
Current consumption	350 mA

Physical

Physical dimensions	210 x 300 x 55 mm
Net weight	1011 g

Environmental

Operating temperature	-25 to 55 °C
IP rating	IP54

Material

	Polycarbonate (3 mm)
--	----------------------

Sounder

	Double piezo
--	--------------

PCB protection

	Fully potted
--	--------------

Tamper & pry-off

	Yes
--	-----

Power supply

	10.0 to 14.5 VDC
--	------------------

Standby current (typical)

	40 mA (with NiCd battery)
	20 mA (without battery)

Operating current (typical)

	350 mA
--	--------

Sound output

	114 dB
--	--------

Frequency

	0.5 to 3 kHz
--	--------------

Operating temperature

	-25 to +55°C
--	--------------

Flash frequency

	50 to 60 flashes/min
--	----------------------

Cut-off timer

	3 min, 5 min, 10 min, 20 min
--	------------------------------

Comfort LED

	Yes
--	-----

Dimensions (W x H x D)

	210 x 300 x 55 mm
--	-------------------

Low voltage detection

	Yes
--	-----

Metal inner cover

	Optional
--	----------

On-board self-activating battery

	10.8 V / 280 mAh
--	------------------

