



AS600FLASH

Flash module for AS 600 Series

Details

- Attractively shaped housings
- High-quality dual skinned design
- 120 dB @ 1 m sound output
- 300 x 210 x 87 mm
- Lead acid battery back-up for up to 7.2 Ah
- Steel inner cover with foam resistant grid
- Fully potted electronics
- Pry-off and opening tamper detection
- Strobe flash light
- Self detection of cable cutting or tampering
- Installer friendly
- Automatic polarity selection
- Independent hold-off for both beacon and siren
- Choice of cut-off time

AS600FLASH

Flash module for AS 600 Series

Technical specifications

General

Accessory group	Siren
Type	Spare part

Electrical

Operating voltage	13 to 14.2 V
Current consumption	700 mA

Physical

Physical dimensions	300 x 210 x 87 mm
---------------------	-------------------

Environmental

Operating temperature	-25 to 55 °C
-----------------------	--------------

Power supply

10.5 to 13.8 VDC

Standby current

N/A

Current consumption

700 mA

N/A

Tamper monitoring relay

N/A

Sound output at 1 m

110 dB

Frequency

0.7 to 1.2 kHz

Cut-off timer

N/A

Operating temperature

-25 to +55°C

Self-activating (with battery)

N/A

Recommended battery

N/A

Material

Polycarbonate/Inox

Weight

3 kg

Dimensions

300 x 210 x 87 mm

Beacon for all types

Supply voltage	13.0 to 14.2 VDC
Operating current	110 mA
Light output	100,000 peak lumens
Flash frequency	60 flashes/minute
Spike suppression network	Standard fitted



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 11 February 2019 - 19:12