Product data sheet



AS630

Outdoor siren with single amber beacon, inox cover



Details

- Attractively shaped housings
- High-quality dual skinned design
- 120 dB @ 1 m sound output
- Lead acid battery back-up for up to 7.2 Ah
- Steel inner cover with foam resistant grid
- Fully potted electronics
- Pry-off and opening tamper detection
- Strobe flash light
- Self detection of cable cutting or tampering
- Automatic polarity selection
- Independent hold-off for both : beacon & siren
- Choice of cut-off time

AS630

Outdoor siren with single amber beacon, inox cover

Technical specifications

General	
Accessory group	Siren
Туре	Outdoor siren
Sounder output (dB @ distance)	120 dB at 1 m (typical)
Flash specification	s
Light output	100,000 peak lumens
Flash frequency	60 flashes/minute
Electrical	
Operating voltage	13 to 14.2 V
Current consumption	600 mA
	25 mA (standby current)
	110 mA (operating current)
Physical	
Physical dimensions	210 x 300 x 87 mm (W x H x D)
Net weight	3 kg
Material	Inox
Environmental	
Operating temperature	-25 to 55 °C

As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

