

# AS700

## Outdoor hardwired siren - EN 50131-4 & NFA2P Grade 3 approved

### Overview

---

The sounder provides a maximum sound output of 112 dBA and offers a host of features including silent engineer start-up, front & rear tamper, low current consumption, diagnostic fault LED, Ring Line monitoring and a battery test feature (with fault output).

The electronics modules are conformal coated to provide additional protection from harsh environments thus ensuring a long working life.

### Certified to the latest European standards

---

The sounder fully meets and is certified to the requirements of EN50131-4:2009 Grade 3, supporting the new functional and operational features now required.



### Details

---

- Certified to NFA2P Grade 3, Environmental class IV
- Long working life
- Easy installation and maintenance
- Low current consumption, standby and alarm
- Replaceable internal battery
- Selectable cut-off timer, Silent Engineer start-up mode
- 3 year warranty

# AS700

## Outdoor hardwired siren - EN 50131-4 & NFA2P Grade 3 approved

### Technical specifications

---

#### General

---

Accessory group	Siren
Type	Outdoor siren
Sounder output (dB @ distance)	112 dB at 1 m (typical)

---

#### Electrical

---

Operating voltage	9 to 15Vdc
Power supply type	VDC

---

#### Physical

---

Physical dimensions	350x200x75
Net weight	1.1Kg
Colour	White
Material	ABS

---

#### Environmental

---

Vandal proof	Yes
Environment	Outdoor

---

#### Standards & regulation

---

Compliance	CE
Certification	EN50131 Grade 3, NFA2P

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 22 April 2021 - 17:40