

# ATS1190

## Smart card reader with 2.5 m cable

### Product overview

---

The ATS1190 smart card readers connect directly on the RS485 data bus of the control panel or 4-Door Controller and may be configured and addressed via a LCD keypad. Some security options (Site code & 4-byte security code) are only programmable via TITAN and configuration cards. The ATS1190 is supplied standard with a white removable dress cover, which can be interchanged with one of four other colours available (see Ordering Information).

### High quality cards & key fobs

---

Both the smart chip and antenna are embedded inside the cards & fobs. Printing is possible on the cards using any industry standard printer. The ATS1472 cards feature a programmable magnetic stripe for Time & Attendance or other applications.

### Security features

---

The ATS smart card technology has the ability to program a unique 268 million, 4-byte, combination security code (values from 0 through 127 are applicable for EMEA). This allows the memory card to unlock/open/disarm based on three keys; the card number, the Site code and the 4-byte security code. Once a 4-byte security code has been created, downloaded to the programmer and the cards, it is not possible to read the memory on the card or even recognise the card memory at any other reader or TITAN and programmer combination. Communications between TITAN and the programmer may also be password protected to prevent the 4-byte security code from being uploaded from the programmer into another PC running TITAN.

### Read/Write encryption

---

The ATS Smart card technology also features an exclusive read/write encryption. When a card is presented at a reader, data are downloaded into the reader, encrypted and re-written back into the card. The readers can also be configured to operate in stand-alone or connected to control devices like office equipment or vending machines. This function enables credits to be assigned on user cards and deducted by the readers, purely on a usage basis. Up to 65535 credits may be allocated in up to 4 different banks with 16 access levels and 4 locations. The reader determines of which bank credits have to be deducted and the number of credits per valid presentation.

### Multiple card badging

---

The ATS1190 smart card reader can be used for arming/disarming areas as well as for access applications. It is suitable for using the multiple card badging techniques which are available for the advisor MASTER control panel family. A user could arm the system in the evenings by badging his card three times within 10 seconds interval. Another application could be for doors which can be programmed so that badging once unlocks, badging twice with the same card keeps the door unlocked to allow people in and out without card, and badging three times re-locks the door.



### Details

---

- Full epoxy filled weather proof construction
- Standard white snap-on cover (optional red, black, beige, grey)
- Specified cable: Aritech WCAT 52/54 or equivalent

# ATS1190

## Smart card reader with 2.5 m cable

### Technical specifications

---

#### Technology

---

|   |                       |
|---|-----------------------|
| Reader type                             | Proximity, Smart Card |
| Reader operating-transmitting frequency | 125 KHz               |
| Supported technology                    | HiTag 2<br>125 kHz    |

---

#### System

---

|                               |   |
|-------------------------------|---|
| Reading distance              | 6 to 8 cm   |
| Max. reader distance to panel | 1.5 km  |
| Supported card types          | HiTag2  |
| Addressing type               | Card Addressing, Keypad Addressing, Software Addressing |
| No. of LEDs                   | 1 blue LED, 1 red LED                                   |
| No. of covers included        | 1 white cover   |
| Reader accessory              | Optional Color Covers                                   |

---

#### Interface & connections

---

|                |                     |
|----------------|---------------------|
| Interface      | ATS RS-485, Wiegand |
| Connector type | Pigtail             |
| Pigtail length | 250 mm              |

---

#### Inputs/outputs

---

|         |                          |
|---------|--------------------------|
| Inputs  | Request to exit          |
| Outputs | 1 Open Collector (25 mA) |

---

#### Tamper type

---

|                |     |
|----------------|-----|
| Pry-off tamper | Yes |
|----------------|-----|

---

#### Operation

---

|            |    |
|------------|----|
| PIN keypad | No |
|------------|----|

---

#### Electrical

---

|                     |                             |
|---------------------|-----------------------------|
| Operating voltage   | 9 to 14 VDC                 |
| Current consumption | 25 mA typical<br>80 mA max. |

---

#### Physical

---

|                     |                  |
|---------------------|------------------|
| Physical dimensions | 36 x 110 x 20 mm |
| Colour              | White            |
| Material            | Plastic          |
| Mounting Type       | Surface mount    |

---

#### Environmental

---

|                       |                   |
|-----------------------|-------------------|
| Vandal proof          | No                |
| Operating temperature | -35 to +66°C      |
| Relative humidity     | 93% noncondensing |
| Environment           | Indoor / Outdoor  |
| IP rating             | IP54              |

---

As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 7 June 2021 - 9:12

