

DC138S60

Industrial flush mount contact for steel door, high security grade 3, white, 6m cable

Requirements for grade 3 magnetic contacts

The grade 3 magnetic contacts are high security contacts which do meet the following requirements: preciseness of opening distance, magnet polarisation, strength of the magnet

Model with built in EOL resistors available

Though built in EOL resistors are not mandatory according to EN50131-2.6 requirements, Interlogix offers a model with built in EOL resistors for a quick installation (see how to Order information)



Details

- EN 50131-2-6 Grade 3 and VDS certified
- 6 m cable
- Tamper protected
- Several European certifications

DC138S60

Industrial flush mount contact for steel door, high security grade 3, white, 6m cable

Technical specifications

General

Application type	Recessed Mount
Contact type	1 pin NC contact
Connectivity	LIYY 4 x 0.14 mm Cu tin-plated; Suitable for LSA IDC method of termination

Wired/wireless

Wired-wireless	Wired
----------------	-------

Electrical

Operating voltage	max. 40 V (permissible operating voltage)
Voltage	max 100V DC
Contact power	max 6W or 6 VA
Switching current	max 500mA
Contact resistance	max 0.15 Ohm

Physical

Physical dimensions	Ø 3.2 mm x 6 m (cable dimensions)
Colour	White
Material	ABS
Dimensions magnet	6 x 19 mm
Dimensions contact / sensor	8 x 32 mm with installation flange EF 8/20
Operating gap	12 mm

Environmental

Operating temperature	-25 to 70°C
IP rating	IP67 class 3

Standards & regulation

EN50131 grade	Grade 3
---------------	---------