

# DD666-D

## 20 m ceiling mount Dual motion sensor, Germany

### 18 curtains of detection

---

The DD600 series complement the successful EV600 series PIRs with dual technology motion sensors. The 18 curtains offer a maximum detection capability, including full under crawl detection, throughout a protected area of up to 20m in diameter.

The unique mirror optics technology is a gliding focus, which creates continuous curtains that never loses track of the intruder.

### 4D signal processing

---

4D signal processing makes an effective discrimination between intruder and false alarm signals. Recognizing the diversity in security applications, the DD600 series features both 4D signal processing and Bi-curtain processing for the harsher environments.

The combination of mirror optics with 4D signal processing not only provides better detection but also increased stability and rejection of false alarms.

### Range Controlled Radar

---

The DD600 sensors incorporate a unique radar technology that is range controlled and operates on 5.8GHz frequency. The range control means that no nuisance alarms are generated for movements beyond the detection pattern.

### Flush Mounting

---

The EV600 and DD600 motion sensors can be flush mounted with the optional accessory 360FM. The 360FM ensures a neat integration in the ceiling, making only the top part of the sensor visible.



### Details

---

- Dual motion sensor
- Step & Gliding Focus Multi Curtain mirror optic
- Range controlled radar on 5.8 GHz
- Plug-in electronics
- Sealed optics
- 4D processing for reduced nuisance alarms
- Selectable coverage pattern using mirror masks
- Additional bi-curtain processing for harsh environment
- No adjustment required for different mounting heights
- EN50131-2-4 Grade 2 certified
- Several European approvals

# DD666-D

## 20 m ceiling mount Dual motion sensor, Germany

### Technical specifications

---

#### General

---

Technology	Dual
Application type	Ceiling Mount
Anti masking	No
Pet immune	No
Camera	No
Pry-off tamper kit	ST400 (optional)

---

#### Detection

---

Max. detection range	20 m
Detection range	20 m / 12 m 65 ft / 39 ft
Coverage (field of view)	360°
Undercrawl protection	Yes
No. of curtains	18
Microwave frequency (nom.)	5.8 GHz
Max. microwave output (at 1m)	0.003 $\mu$ W/cm <sup>2</sup>
Alarm memory	Yes
Alarm time	3 s
Target speed range	0.2 to 3.0 m/s
Peak-to-peak ripple immunity	2V (at 12 VDC)

---

#### Wired/wireless

---

Wired-wireless	Wired
----------------	-------

---

#### Inputs/outputs

---

Alarm relay characteristic	NC, 80 mA 30 VDC, Form C
Tamper relay characteristic	NC, 80 mA 30 VDC, Form C
Remote control lines	Day/Night, Walk test

---

#### Electrical

---

Operating voltage	9 to 15 VDC
Power supply type	12 VDC
Current consumption	12 mA

---

#### Physical

---

Physical dimensions	138 x 92 mm
Colour	White
Mounting height	2.5 to 5 m

---

#### Environmental

---

Operating temperature	- 10 to 55°C
Relative humidity	95 % relative humidity
Environment	Indoor

---

#### Standards & regulation

---

EN50131 grade	Grade 2
---------------	---------

---

As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 18 May 2021 - 15:14

