

# DD666AM-D

**Dual/AM detector with 18 curtains of 20m, CO relay, VdS class-B certified**

## 18 curtains of detection

---

The DD600 series complement the successful EV600 series PIRs with dual technology motion sensors. The 18 curtains offer a maximum detection capability, including full under crawl detection, throughout a protected area of up to 20m in diameter.

The unique mirror optics technology is a gliding focus, which creates continuous curtains that never loses track of the intruder.

## 4D signal processing

---

4D signal processing makes an effective discrimination between intruder and false alarm signals. Recognizing the diversity in security applications, the DD600 series features both 4D signal processing and Bi-curtain processing for the harsher environments.

The combination of mirror optics with 4D signal processing not only provides better detection but also increased stability and rejection of false alarms.

## Range Controlled Radar

---

The DD600 sensors incorporate a unique radar technology that is range controlled and operates on 5.8GHz frequency. The range control means that no nuisance alarms are generated for movements beyond the detection pattern.

## Flush Mounting

---

The EV600 and DD600 motion sensors can be flush mounted with the optional accessory 360FM. The 360FM ensures a neat integration in the ceiling, making only the top part of the sensor visible.



## Details

---

- Dual motion sensor
- Step & Gliding Focus Multi Curtain mirror optic
- Range controlled radar on 5.8 GHz
- Plug-in electronics
- Sealed optics
- 4D processing for reduced nuisance alarms
- Selectable coverage pattern using mirror masks
- Additional bi-curtain processing for harsh environment
- No adjustment required for different mounting heights
- EN50131-2-4 Grade 3 certified
- Several European approvals

# DD666AM-D

Dual/AM detector with 18 curtains of 20m, CO relay, VdS class-B certified

## Technical specifications

---

### General

Technology	Dual
Anti masking	Yes
Pet immune	No
Camera	No
Pry-off tamper kit	ST400 (optional)

### Detection

Max. detection range	20 m
Detection range	12 m / 20 m 65 ft / 39 ft
Coverage (field of view)	360°
Undercrawl protection	Yes
No. of curtains	18
Microwave frequency (nom.)	5.8 GHz
Alarm memory	Yes
Target speed range	0.2 to 3.0 m/s

### Wired/wireless

Wired-wireless	Wired
----------------	-------

### Inputs/outputs

Alarm relay characteristic	NC, 80 mA 30 VDC, Form C
Tamper relay characteristic	NC, 80 mA 30 VDC, Form C
Anti mask relay characteristic	NC, 80 mA 30 VDC, Form C
Remote control lines	Day/Night, Walk test

### Electrical

Power supply value	9 to 15 VDC
Current consumption	12 mA (nom.)

### Physical

Physical dimensions	138 x 92 mm
Mounting height	2.5 to 5 m

### Environmental

Operating temperature	-10° to +55° C
Relative humidity	95% relative humidity
Environment	Indoor

### Standards & regulation

EN50131 grade	Grade 3
---------------	---------

As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 22 April 2021 - 18:22

