



# DDV1016AM-D-B

## 16m 50ft Dual 9C AM VdS/EN Grade III Black

### Patented Range Gated Radar Technology

---

Motion sensors of the DD1000 Series incorporate a UTC Fire & Security patented and unique range gated radar technology allowing the installer to define a clear borderline of the radar range as the radar is used to measure distance between the sensor and moving objects. Effectively the end-user will get rid of any nuisance alarms generated by movements outside the detection pattern.

Every motion sensor comes with 4 possible radar ranges selectable via dip switches allowing the detection pattern to be tailored according to the room where the motion sensor is installed.

The radar operates on 5.8GHz frequency and will not interfere with any WIFI networks.

### PIR Technology in combination with patented mirror optics

---

Our patented optical mirror technology gives the advantage of gliding focus, which creates a continuous detection curtain from floor level up to installation height.

Within our DDV1016 series we are using a dual element pyro generating 2 volumetric curtains for each of the 9 curtain sets.

### Detection technologies working together

---

These dual tech motion sensors generate an alarm depending on what both technologies – range gated radar and PIR – saw within its detection coverage.

But our dual tech go beyond a simple “AND” function : it classifies the signals from each technology – range gated radar and PIR – to have the best alarm result without being sensitive for nuisance signal sources. This technology creates a uniform sensitivity in all course directions.

### Ease and flexibility of installation

---

1. Tolerates wall angle deviation and different mounting heights.
2. Limited loss of coverage when objects are placed in the field of the PIR vision.
3. Easy range setting via dip switches of the range gated radar in order to tailor the detection pattern to your needs.
4. Multiple build-in End-Of-Line resistor values with “easy wiring” option available.
5. Plug-in connector.

### Anti-masking (optical and radar)

---

The use of Active Infrared and radar technology results in a superior anti-masking functionality that supervises the motion sensor on the inside and outside. Radar verification prevents from having unwanted AM alarms caused by e.g. insects. In advanced setting the AM alarm is held until the effective source of the anti-masking (e.g. spray, tape,...) has been removed. Even partial masking – so going beyond the EN Grade III standard – will be detected when in advanced setting.

### Details

---

- Patented selectable range gated radar technology clearly defining the radar detection border
- PIR technology with patented mirror curtain optics
- Anti-masking variant using Active Infrared and radar technology to protect against sabotage actions outside and inside of the motion sensor
- Intelligent alarm decision based on signal classification of the PIR and radar alarm
- Automatic continuous self diagnostics on all technologies
- Green mode : option to switch off the radar technology when the security system is not armed

## **Other members of the family**

---

This family includes motion sensors with variants in detection range, two types of anti-masking masking technology and Pet Immunity. The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.

# DDV1016AM-D-B

## 16m 50ft Dual 9C AM VdS/EN Grade III Black

### Technical specifications

---

#### General

---

Technology	Dual
Anti masking	Yes
Pet immune	No
Camera	No
Pry-off tamper kit	On board
Detector start-up time	60 sec

---

#### Detection

---

Max. detection range	16 m
Detection range selection	10, 12, 14, or 16 m selectable via dip switches selection
Coverage (field of view)	78°
Undercrawl protection	Yes
No. of curtains	9
Microwave frequency (nom.)	5.8 GHz
Max. microwave output (at 1m)	0.003 $\mu$ W/cm <sup>2</sup>
Alarm memory	Yes
Alarm time	3 s
Target speed range	0.1 to 4.0 m/s
Peak-to-peak ripple immunity	2 V (at 12 VDC)

---

#### Wired/wireless

---

Wired-wireless	Wired
----------------	-------

---

#### Inputs/outputs

---

Alarm relay characteristic	NC, 80 mA 30 VDC, Form A
Tamper relay characteristic	NC, 80 mA 30 VDC, Form A
Anti mask relay characteristic	NC, 80 mA 30 VDC, Form A
Remote control lines	Day/Night, Walk test

---

#### Electrical

---

Operating voltage	9 to 15 VDC
Current consumption	10 to 22 mA (11 mA nom.)

---

#### Physical

---

Physical dimensions	126 × 63 × 50 mm
Net weight	120 g
Colour	Black
Mounting height	2 to 3 m

---

#### Environmental

---

Operating temperature	-10 to +55 °C
Relative humidity	95% max. non-condensing
Environment	Indoor
IP rating	IP30

---

#### Standards & regulation

---

Certification	EN50131 Grade 3, VdS
---------------	----------------------

---

As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 22 April 2021 - 18:22

