

EV1116AM

16 m volumetric PIR/AM motion sensor

The power of mirror

Aritech motion sensors have the most advanced and sophisticated optics in the security industry. This unique optical mirror technology is a step and gliding focus, which creates a continuous curtain resulting in a sensor that never loses track of the object.

To increase detection coverage, the EV1100 series sensors incorporate a 3-step gliding focus, which produces 11 continuous curtains to detect infrared signals up to a 16m distance.

5D signal processing

"5D" is the next generation of Aritech signal processing. It builds on the current strengths of 4D, but adds an intelligent differentiation between fast and slow moving signals.

When a slow thermal source is detected, the signal processing switches automatically to the 5D mode and executes additional pattern recognition to distinct this signal from a slow walking person. If the signal fits, it must be an intruder and an alarm is generated. If there is no fit, the signal is ignored, which ensures signals such as moving reflection of sunlight are filtered out.

The result is a unique combination of high sensitivity detection with high false alarm immunity without the need for manual sensitivity adjustment.

Easy to install

PIRs of the 1000 series are the most rewarding sensors to install:

1. Tolerate wall angle deviation and different mounting heights.
2. Limited loss of coverage when objects are placed in the field of vision.
3. No range setting is required thanks to constant range sensitivity.
4. Plug-in electronics.

Complete family

The 1000 series are part of the Aritech range of motion sensors. This family includes motion sensors with variants in housing size, detection range, anti-masking, dual detection technology, addressable interfacing, wireless transmission and more. This range covers all applications where security needs to be safeguarded.

The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.



Details

- Passive Infra Red motion sensor
- Automatic reporting of all masking attempts
- 3Brid Step & Gliding Focus Curtain mirror
- Plug-in electronics
- Sealed optics
- "5D" signal processing for false alarm immunity
- Cloak and umbrella immunity
- Full under crawl detection
- Selectable coverage pattern using mirror masks
- Auto focus with constant range sensitivity
- No adjustment required for different mounting heights
- Tolerates wall angle deviation
- Certified EN50131-2-2 Grade 3
- Several European approvals

EV1116AM

16 m volumetric PIR/AM motion sensor

Technical specifications

General

Technology	PIR
Anti masking	Yes
Pet immune	No
Camera	No
Signal processing	5D
Pry-off tamper kit	On board

Detection

Max. detection range	16 m
Coverage (field of view)	86°
Undercrawl protection	Yes
No. of curtains	11
Alarm memory	Yes

Wired/wireless

Wired-wireless	Wired
----------------	-------

Inputs/outputs

Alarm relay characteristic	NC when energised (voltage free)
Tamper relay characteristic	NC when cover closed (voltage free)
Remote control lines	Day/Night, Walk test

Electrical

Operating voltage	9 to 15 VDC
Current consumption	11 mA

Physical

Physical dimensions	125 x 65 x 60 mm
Colour	White
Mounting height	1.8 to 3 m

Environmental

Operating temperature	- 10 to 55°C 14 to 130°F
Relative humidity	95 % relative humidity
Environment	Indoor

Standards & regulation

EN50131 grade	Grade 3
---------------	---------



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 22 April 2021 - 18:08

