

# GS321

## Piezo glassbreak detector with relay output 6 m

### High Performance

---

The glassbreak detector GS321 with relay output is designed to detect the specific ultrasonic frequency range produced by breaking glass. Knocks and other normal disturbances to a windowpane do not trigger an alarm.

Suitable for use on standard window glass or plate glass the GS321 provide a 2 meter radius of protection. The detector may be fitted as close as 2 cm from the window frame and still provide a full 2 metre radius of coverage on standard glass. The detector is moulded into a plastic housing and delivered with 6m cable. They are featuring a built-in latch LED indicator for easy location of alarmed detectors.



### Details

---

- Small and unobtrusive
- Latching alarm indication
- 2m radius protection
- Easy to install
- No adjustment
- Tamper proof

# GS321

## Piezo glassbreak detector with relay output 6 m

### Technical specifications

---

#### General

Technology	Piezo
Glass types	Plate
Range	6 m radius
Tamper switch	No

#### Wired/wireless

Wired-wireless	Wired
----------------	-------

#### Electrical

Power supply value	9 to 18 VDC
Current consumption	4 mA @ 6 VDC 5mA @ 12 VDC

#### Physical

Physical dimensions	37 x 19 x 12 mm
Net weight	50 g
Colour	White
Mounting type	Surface mount

#### Environmental

Operating temperature	-25 to +70°C
IP rating	IP67

