

IM1640PAG

Surface mount contact, armoured cable, NFA2P

Commercial surface mount contact

The IM1640 series commercial surface mount contacts are specifically designed to work on metal frames. The contacts can be used in harsh environments. Special version with armoured cable and including junction box is available.



Details

- Designed for use in harsh environments
- Magnet specifically designed to work on metal frames
- Tamper loop
- Version with armoured cable

IM1640PAG

Surface mount contact, armoured cable, NFA2P

Technical specifications

General

| | |
|------------------|---------------------------------|
| Application type | Surface Mount |
| Contact type | NC |
| Connectivity | 4 wires, 60 cm (armoured cable) |

Wired/wireless

| | |
|----------------|-------|
| Wired-wireless | Wired |
|----------------|-------|

Electrical

| | |
|---------|-------------|
| Voltage | max. 48 VDC |
|---------|-------------|

Physical

| | |
|-----------------------------|-----------------------------|
| Physical dimensions | 72 x 23 x 19 mm (W x H x D) |
| Colour | White |
| Dimensions magnet | 23 x 72 mm |
| Dimensions contact / sensor | 23 x 72 mm |
| Operating gap | 25 mm |

Environmental

| | |
|-----------------------|--------------|
| Operating temperature | -10 to +55°C |
|-----------------------|--------------|

