

PB16

1.5m - 360° AIR Beam Tower (double sided) including installation kit.

Pillar packing list

1. Top/bottom cover : 2 pcs
2. Polycarbonate cover : 2 pcs
3. Aluminium profile : 1 pcs
4. Tamper plate : 1 pcs (EP1)
5. Tamper : 1 pcs (EP1)
6. M3 DIN 934 : 2 pcs (EP1)
7. M3x16 DIN 84 : 2 pcs (EP1)
8. M4x8 DIN 84 : 4 pcs (EP4)
9. M4x20 DIN 933 : 2 pcs (EP2)
- 10.M4 DIN 934 : 16 pcs (EP4) (C3)
- 11.M4 DIN 985 : 2 pcs (EP2)
- 12.M4 DIN 125 : 2 pcs (EP2)
- 13.Spacer : 2 pcs (EP2)
- 14.Cable gland PGM16 : 2 pcs (EP4)
- 15.Cable gland PGM20 : 2 pcs (EP4)
- 16.M8x16 DIN933 : 4 pcs (TA3)
- 17.Side bracket <2m : 2 pcs
- 18.M8 DIN 985 : 4 pcs (TA3)
- 19.M8 DIN 125 : 4 pcs (TA3)
- 20.M4x12 DIN 7985 : 12 pcs (C3)
- 21.Bracket : 6 pcs
- 22.dia.2.9x16 DIN 7981 : 12 pcs (C3)
- 23.Anchor bolt : 4 pcs (MAN2)



Details

- 1.5m height
- 360° view
- CE certified product

PB16

1.5m - 360° AIR Beam Tower (double sided) including installation kit.

Technical specifications

General

Accessory group	Perimeter / Outdoor
Type	Mounting

Electrical

Operating voltage	12 to 24 V
Power supply type	VDC

Physical

Physical dimensions	1470 x 130 x 260 mm
Net weight	5.70 kg

Environmental

Operating temperature	-15 to 50 °C
-----------------------	--------------

Voltage

12 to 24 VDC

Angle of view

360°

Tamper switch output

CO (change over)

Operating temperature

-15 to +50°C

Material

Aluminium, plastic (polycarbonate, ABS)

Dimensions (HxWxD)

147 x 13 x 26cm

Weight

5.70 kg



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 3 July 2020 - 17:51