

# PB611M

AIR Line Detector, 4 Lines, 100 m Outdoors, without housing



## Details

---

- Range 100 metres
- Outdoor installation
- 4 Synchronised lines
- 4 Optional frequency steps ensure that one receiver will only 'see' one transmitter
- Adjustable precision optics
- Immune to external light
- High protection against EMC noise
- AGC sensitivity control
- Extra lens heater available as an accessory
- Full range of tower accessories for outdoor fitting
- Visibility control is standard
- Tone signal for correct adjustment
- Alarm memory
- Only to be used for pillar mount

# PB611M

## AIR Line Detector, 4 Lines, 100 m Outdoors, without housing

### Technical specifications

---

#### General

Category	Active Infrared Beams
Product type	Active Infrared Beam
Infrared system	4-beam LED, double frequency modulation
Tamper	NC (max. charge 30 VAC/VDC - 100 mA)

#### Detection

Range	100 m
Alarm response time	51 to 700 ms

#### Inputs/outputs

Alarm output	NC/NO (max. charge 30 VAC/VDC - 0.5 mA)
Supervision output	NC/NO (max. charge 30 VAC/VDC - 1 A)

#### Electrical

Power supply value	12 to 30 VDC
Current consumption	70 mA

#### Physical

Physical dimensions	104 x 390 x 98 mm
Net weight	1.2 kg
Colour	Black

#### Environmental

Operating temperature	-35 to +66°C
Environment	Outdoor



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 3 July 2020 - 12:54