

RF-DC101B-K4

WIRELESS SURFACE MOUNT DWS, MAHOGANY, 433Mhz, 80+

In this series we are using UTC's 80+ wireless protocol in a 433Mhz frequency set-up, which allows for a better wireless indoor range. This 80+ protocol also helps ensure security approvals.

This wireless door window sensor, which has 2 reed switches, protects anything that opens and closes such as doors, windows and cabinets. You can monitor any supervised contact in such a way that hardwired devices become wireless in a fraction of time.

The sensor is equipped with a wall and cover tamper for additional security.

This series comes in a white and a mahogany version and also has accessories in both colors.



Details

- 80+ wireless protocol using 433Mhz for improved indoor range
- 5-years battery life
- Battery pull-tab concept
- Selectable reed switches
- Additional terminal block
- Range of accessories : two types of spacers and a stronger magnet
- Holding EN and Incert certificates

RF-DC101B-K4

WIRELESS SURFACE MOUNT DWS, MAHOGANY, 433Mhz, 80+

Technical specifications

General

Application type	Surface Mount
------------------	---------------

Wired/wireless

Wired-wireless	Wireless
Wireless frequency	433 MHz LoNa
Open-air range	400 m

Electrical

Power consumption	max 70 mA at 3V
Voltage	3.0 V
Contact power	Maximum power output : 10mW
Batteries	1300 mAh (DL123A)
Battery lifetime	>5 years with supervis. signal per 15 min. and 4 activations/hour

Physical

Net weight	59 g
Colour	Mahogany
Dimensions contact / sensor	101 x 31 x 28 mm
Operating gap	7-13 mm

Environmental

Operating temperature	-10° to +55° C
Storage temperature	-34 to 60 °C
Relative humidity	0 to 90% noncondensing

Standards & regulation

EN50131 grade	Grade 2
---------------	---------



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 22 April 2021 - 18:08