

RF903I4

Acoustic glassbreak Detector RF433 MHz



Details

- Provides 360-degree coverage
- Can be mounted on a ceiling, opposite wall or adjacent walls
- Range of up to 6 meters

RF903I4

Acoustic glassbreak Detector RF433 MHz

Technical specifications

General

Technology	Acoustic
Range	Max. 6 m radius for glass panes of at least 0.5 x 0.6 m
Tamper switch	Yes
Glass types and thickness	Plate : 2.4 to 6.4 mm / Tempered : 3.2 to 6.4 mm / Laminated : 3.2 to 6.4 mm

Wired/wireless

Wired-wireless	Wireless
Wireless frequency	433 MHz legacy
Open-air range	150 m

Electrical

Operating voltage	2.6 to 4.5 VDC
Current consumption	26 µA typical average
Batteries	2 x 3.0 V Lithium DL123A
Battery lifetime	5 years
Maximum power output	10 dBm e.r.p.
Transmitter conditions	alarm, tamper and low battery supervisory

Physical

Physical dimensions	108 x 79 x 31 mm
Colour	White
Mounting type	Surface mount

Environmental

Operating temperature	0° to 50°C
Storage temperature	-34° to +60°C
Relative humidity	90%

Standards & regulation

Compliance	CE
------------	----



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 22 April 2021 - 18:08