



# SMA-L-BIO

**MA SIGMA Lite - Bio, MoNo-factor Bio only, IP65, 500 users, CE**

## **MA SIGMA Lite & MA SIGMA Lite Plus Series**

---

Engineered with the same attention to detail and performance as their predecessor, the MorphoAccess® SIGMA Lite terminals are specifically designed to equip narrow mounting surfaces, such as glass/aluminum door Mullions, turnstiles or server rack doors. With two designs (with touchscreen: MA SIGMA Lite Plus ; without touchscreen: MA SIGMA Lite) and multiple embedded card reader options, there are a variety of models to address the widest range of deployment scenarios, both indoor and outdoor.

## **Embedded web server**

---

The MA SIGMA Lite Series enables on-device enrollment, terminal configuration and transaction log retrieval thanks to the embedded web server. Moreover, it can be used with any device (PC, laptop, tablet, smartphone), any operating system (Windows, Android, iOS) or any web browser (Google Chrome, Mozilla Firefox, Safari and Internet Explorer).

## **Enhanced interactivity**

---

Thanks to the 2.8" QVGA touchscreen on the MA SIGMA Lite Plus Series, you can benefit from an enhanced user experience. The MA SIGMA Lite Plus holds T&A in and out function keys, User ID/PIN/BioPin management and intuitive icons and live messages.

## **Compatible with existing installations**

---

The MA SIGMA Lite Series can be used to upgrade an existing installation or to complement the installation with MorphoAccess® SIGMA (Lite) devices using the MorphoManager application or MIK SDK on a Morpho network or the SecureAdmin™ application or SecureSDK™ on a BioCrypt network.

## **Enhanced security features**

---

The MA SIGMA Lite Series encompasses the latest and greatest anti-fraud features, such as: fake finger detection, duress finger, timed anti-pass back function and banned/authorized user lists.

## **Details**

---

- Leading fingerprint technology inside - 1:10,000 user identification in 1 second
- High capacity - 30,000 templates, 250,000 IDs in authorized user list, 1 million logs
- Advanced anti-fraud features
- Flexibility - Optional Prox, iCLASS or MIFARE/DESFire/NFC contactless card reader
- Tough design - IP65 rated and vandal resistant (IK08, SIGMA Lite only)

# SMA-L-BIO

MA SIGMA Lite - Bio, MoNo-factor Bio only, IP65, 500 users, CE

## Technical specifications

---

### Technology

Reader type	BioMetric
-------------	-----------

---

### System

Max. reader distance to panel	Ethernet: 100 m, RS485: 1219 m
-------------------------------	--------------------------------

---

RTE (Request To Exit)	No
-----------------------	----

---

CSN (Card Serial Number)	No
--------------------------	----

---

Custom data model	No
-------------------	----

---

No. of LEDs	1
-------------	---

---

### Biometric

Biometric type	Fingerprint
----------------	-------------

---

Biometric sensor type	Optical
-----------------------	---------

---

### Interface & connections

Interface	Ethernet, OSDP V2, OSDP V2 Secure Channel, RS-485, USB, Wiegand
-----------	---

---

Connector type	Network, Pigtail
----------------	------------------

---

Pigtail length	30 cm
----------------	-------

---

### Tamper type

Pry-off tamper	No
----------------	----

---

Opening tamper	Yes
----------------	-----

---

### Operation

Stand-alone	Yes
-------------	-----

---

PIN keypad	No
------------	----

---

### Electrical

Power supply type	PoE in
-------------------	--------

---

Power supply value	12 to 24 VDC
--------------------	--------------

---

### Physical

Physical dimensions	68 x 156 x 62 mm
---------------------	------------------

---

Net weight	280 g
------------	-------

---

Shipping weight	325 g
-----------------	-------

---

Colour	Black
--------	-------

---

Material	Polycarbonate
----------	---------------

---

Form factor	Oversized
-------------	-----------

---

Mounting type	Surface mount
---------------	---------------

---

### Environmental

Vandal proof	No
--------------	----

---

Operating temperature	-20 to +55°C
-----------------------	--------------

---

Storage temperature	-20 to +55°C
---------------------	--------------

---

Relative humidity	10 to 80% noncondensing
-------------------	-------------------------

---

Environment	Outdoor
-------------	---------

---

IP rating	IP 65
-----------	-------

---

	IK 08
--	-------

---

### Standards & regulation

Compliance	CE, FCC, ICASA, REACH, RoHS, UL 294, WEEE
------------	---

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 23 July 2021 - 9:59