

TX-1011-03-1

Slimline door/window sensor 868 MHz, Gen2, white

Installation

This wireless sensor protects anything that opens and closes such as doors, windows and cabinets by means of internal reed switches. You can also choose to use the transmitter to monitor a supervised contact. The sensor is equipped with a wall and cover tamper for additional security.



Details

- Learn-mode technology
- Supervised transmissions
- More than 3 years battery life
- Complies with EN50131-5-3 - approvals pending

TX-1011-03-1

Slimline door/window sensor 868 MHz, Gen2, white

Technical specifications

General

Application type	Surface Mount
------------------	---------------

Wired/wireless

Wired-wireless	Wireless
----------------	----------

Wireless frequency	868 MHz
--------------------	---------

Open-air range	400 m
----------------	-------

Electrical

Batteries	1 x 3 V Lithium
-----------	-----------------

Battery lifetime	3 to 5 years
------------------	--------------

Physical

Colour	White
--------	-------

Dimensions contact / sensor	102 x 32 x 32 mm
-----------------------------	------------------

Operating gap	10 mm max.
---------------	------------

Standards & regulation

EN50131 grade	Grade 2
---------------	---------

Certification	EN50131, F&P, INCERT, NFA2P, REQ
---------------	----------------------------------

