



# WC104W

**Shielded Composite 2 + 2 Cable 2 x 0.75**

## Details

---

- For internal or external wiring of warning network systems
- Manufactured in accordance with BS4737 section 3.30
- Suitable for gluing to surfaces
- High quality PVC

# WC104W

## Shielded Composite 2 + 2 Cable 2 x 0.75

### Technical specifications

---

#### Shielding

Shielded	Yes
----------	-----

---

#### Core

Conductor size	0.22 mm <sup>2</sup> (data) - 0.75 mm <sup>2</sup> (power)
Conductor material	Plain copper
Wire colours	Red, Black (power) Blue, White (data)

---

#### Jacket

Jacket colour	White
Jacket thickness	Min. 0.45 mm <sup>2</sup> - max. 0.7 mm <sup>2</sup>

---

#### Electrical Characteristics

Current rating	1 A
Max.conductor DC resistance	92.4 ohm/km @ +20°C
Nominal (mutual) capacitance	90 pF/m

---

#### Physical

Cable length	100 m
No. of wires	4

---

#### Environmental

Halogen free	No
--------------	----

---

#### Standards & Regulation

Compliancy	CE
------------	----

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 23 July 2021 - 9:46